



euku care oil

1 PRODUCT DESCRIPTION

Impregnating oil. Wood floor care for oxidative impregnated-oiled floors.

- Wax-free follow-up impregnation based on natural oils.
- High penetration effect.
- Mild smelling.
- Good refreshing of oiled floors.

2 AREAS OF APPLICATION

Deeply effective follow-up impregnation of tired, dry wood and parquet floors in the framework of regular care. The wood regains its color intensity.

Due to its liquid consistency also suitable for impregnating furniture, wood panels, etc.

3 APPLICATION

Clean the floor thoroughly before care treatment with a slightly damp mop. Allow the floor to dry. Saturate the wood corresponding to its absorbent characteristics, e.g. apply the product with an oil roller or a cloth, avoiding any excess oil. After allowing it to soak in for 30 minutes polish out the remaining excess. Do not allow any moist oil to remain on the surface.

Please note:

- Whatever the wood absorbs must be provided. If there is too much oil on top of the wood, this must then be removed.
- It is also advantageous to apply the oil with the T-Wiper and cloth-strip.
- For polishing out on large areas we recommend using a monodisc machine. Recommended pad: green or white. Larger excesses of oil can be soaked up with a cloth laid underneath

4 CONSUMPTION

Depending on the absorbency of the subsurface. Guideline: approx. 30-50 ml/m² (Range: 20-30 m²/l).

Higher consumption is possible in the case of coarse sanding, wider joints and highly absorbent wood, although subsequent applications will use considerably less.

5 DRYING TIME

Can be walked on carefully, or worked on again, after about 16 hours. The area should not be mopped wet in the first 7 days afterwards. After 10 days at the earliest carpets can be laid on the floor.

Low temperatures, increased humidity, poor ventilation and drying inhibiting wood ingredients can extend the drying time substantially.

6 CLEANING / CARE



euku care oil

Please note that the surface image of an oil-impregnated floor is only finalized after use, cleaning and care. After complete hardening, use **euku care emulsion** for cleaning and care and **euku care oil** for subsequent oil care. Please observe eukula care instructions for oil impregnated floors.

7 STORAGE

24 months in an unopened original canister. Remove any skin which may have formed before use. Store in a cool, dry place. Keep out of the reach of children.

8 TECHNICAL DATA

Contains substances: natural oils and waxes, modified vegetable oils, aliphatic solvents, glycole ether, drying agents free of lead and cobalt.

voc (g/l) 474 / GISCODE: Ö60+ / Decopaint 2004/42/IIA(f)(700)700

ADR/RID: not a dangerous good as defined by transport regulations.

CLP: GHS08, Danger. May be fatal if swallowed and enters airways. Information on labelling and on the safe handling of the product can be found in the current Safety Data Sheet.

Even when using low-pollution products, the usual safety measures are to be observed. Keep out of the reach of children. Completely emptied canisters can be disposed of in domestic waste.

8 SPECIAL NOTES

- Warning! Danger of self-combustion of oil-soaked working materials, such as cloths, fleeces, sanding dust, etc. These should be enclosed in an air-tight metal container or soaked with water and disposed of in a fire-safe way. The oil itself is not self-combusting.
- All the details are given under laboratory conditions 23°C/50% rH/ with air changed 3 times per hour. Conditions on site can vary and account for different results. Reference wood: oak.
- Oiled surfaces smell. The smell diminishes with increasing drying in the course of days. In the initial time after an oil treatment ventilate the rooms well.

9 CROSS-REFERENCE

Our following publications in their updated form are valid as an integral part of this fact sheet:

- General notes on the application of eukula finishes
- Safety data sheet available on request.

The quoted printed matter, as well as this product information in its updated form, is available on our homepage www.eukula.com or on request from the address quoted below.

euku care oil



eukula – We Care About Wood Floors

Headquarter
Dr. Schutz GmbH
Holbeinstraße 17
D-53175 Bonn
Tel.: + 49 228 / 95 35 2-40
Fax: + 49 228 / 95 35 2-46
E-Mail: export@dr-schutz.com
www.dr-schutz.com

UK
Dr. Schutz U.K Ltd.
Unit 24, Anglo Business Park,
Smeaton Close, Aylesbury Bucks
HP19 8UP

Contact: Richard Nelson
Tel.: 0044 / 1296 437827
Fax: 0044 / 1296 334219
E-Mail: richard@dr-schutz.com

Ireland
Dr. Schutz Ireland
35 Pic Du Jer Park,
Ballinlough, Cork

Contact: Paul O'Reardon
Mobile: 0877678388
E-Mail:
drschutzireland@gmail.com

North America
Schutz NA LLC
8701 Torresdale Ave
Suite P
Philadelphia PA 19136
USA
Tel.: +1 (877) 272-4889 x 3
Mobile: +1 610-310-2412
sam@dr-schutz.us

The above advice for technical application is given to the best of our knowledge and according to the latest state of technology. Therefore, if our products are used carefully heeding the advice given on their application, as well as following our suggested procedures with the materials intended for use with these products, no damage shall occur. However, our products are used outside and beyond our possible control, and are therefore subject to your own responsibility, which does not release you from the obligation to check for yourself whether our supplied products are suitable for your intended purpose and procedure. Therefore our notes and advice are not legally binding and cannot be used against us as grounds for liability - which includes the rights and protection of any third party. The relevant recommendations, guidelines and standard norms are to be observed, as well as the recognized technical rules. On publication, this product information replaces and supersedes the validity of any previous versions.