

# PRIMER VT PLUS

Primer/vapour barrier for floors and walls in wet rooms



## PRODUCT IDENTITY

**Primer VT Plus** is a latex-based, thixotropic primer/vapour barrier for wet rooms. It is part of a Sintef technically approved TG 2402 and TG 20806 wet-room system and of the VT system, together with **Mapegum WPS** and **Mapeguard WP 2K Membrane**.

## WHERE TO USE

**Primer VT Plus** can be applied to concrete, render, anhydrite screed, plasterboard and cementitious fillers, as well as approved construction boards. It can be applied in wet rooms where there is a requirement of an  $S_D$  value of over 10 m.

## RECOMMENDATIONS

**Primer VT Plus** should not be diluted with water.

## DIRECTIONS FOR USE

### Substrate

The substrate must be clean and dry.

### Application

Apply **Primer VT Plus** with a roller/brush in two coats, with a total consumption of 0.3 kg per m<sup>2</sup>. The coats should be applied at right angles to each other.

**Mapegum WPS** can be applied once the **Primer VT Plus** is dry (approx. 30 minutes at +20°C).

## CLEANING

All equipment used should be cleaned immediately after use with water.

## CONSUMPTION

0.3 kg/m<sup>2</sup>.

## PACKAGING

Primer VT Plus is supplied in 1 kg bottle and 6 and 14 kg tubs.

## STORAGE

Primer VT Plus can be stored for 12 months unopened in its original packaging.  
Primer VT Plus must be stored in a frost-free environment.

## SAFETY INSTRUCTIONS FOR PREPARATION AND INSTALLATION

Instructions for the safe use of our products can be found on the latest version of the SDS available from our website [www.mapei.no](http://www.mapei.no)

PRODUCT FOR PROFESSIONAL USE.

## TECHNICAL DATA (typical values)

### PRODUCT IDENTITY

Colour:	blue
Consistency:	liquid
Density:	approx. 1.25 g/cm <sup>3</sup>
pH:	2 - 3
Dry solid content:	55 %
Viscosity:	tixotropic
EMICODE:	EC1 Plus – very low emission

### PRODUCT APPLICATION DATA (at +20°C, 50 % RH)

Application temperature range:	from +10°C to +40°C
--------------------------------	---------------------

### FINAL PROPERTIES

Ready for coating:	when primer is dry, after approx. 30 minutes
--------------------	--

## WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above - information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

Please refer to the current version of the technical data sheet, available from our web site [www.mapei.no](http://www.mapei.no)

## LEGAL NOTICE

---

*The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at [www.mapei.no](http://www.mapei.no)*

ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.

### Mapei AS

Vallsetvegen 6, 2120 Sagstua, Norge



+47 62 97 20 00



[www.mapei.no](http://www.mapei.no)



[post@mapei.no](mailto:post@mapei.no)

**10205-4-2026-gbxno**

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution.

