



Declaration of Performance
in accordance to Bauprodukteverordnung EU Nr. 305/2011

DOP-Amorim parquet 06-2020

1	AMORIM-Multilayer Parquet Flooring, 14 mm / 15 mm	EN13489: 2017
2	Flooring for interior installation, floating / glue down	
3	AMORIM CORK FLOORING S. A., Apartado 13, PT-4536-907 S. Paio de Oleiros / Portugal	
4	System of assessment and verification of constancy of performance	3

Declared performance

5	Thickness	a) 14 mm b) 15 mm	EN14342: 2013
	Density	≥ 500 kg/m ³	
	Reaction to fire	Dfl-s1	
	Formaldehyd emissions ¹⁾	E1	
	PCP emissions ¹⁾	below detection limit	
	Other harmful ingredianets	not applicable	
	Thermal conductivity	a) 0,105 W/mK b) 0,115 W/mk	
	Slip resistance	not specified	
	Biological durability ²⁾	class 2-5	

The performance of the product identified in point 1. is in conformity with the declared performance in point 5.
This declaration of performance is issued under the sole responsibility of the supplier identified in point 3.

6 Signed for and on behalf of the supplier by:

June 2020
Ragnar Eggers, Head of Branch




AMORIM
AMORIM Revestimentos S.A.
Zweigniederlassung Delmenhorst
Bermer Str. 55 - D-27751 Delmenhorst

7 Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant):
Timber Research and Development Institute Praha
Physical and chemical laboratory
Na Florenci 7-9, 11171 Praha 1, Czech Republic, email: fchl@vvud.cz
www.vvud.cz, phone: +420 221 773 717, Test report: FCHL – 509/14

8 ¹⁾ The test laboratory (7) analysed in accordance to harmonized EU-Norm and issued an appropriate certificate. Due to underlying system of assessment (4), the initial inspection and constant supervision as well as the resulting evaluation has to be achieved by the supplier.

²⁾ oak heartwood: 2-3; pine heartwood: 3-4; poplar: 5; sapwood in general: 5